


Geometric investigations of nonlinear vibrations of elastic systems having one degree of freedom. Isal. po teor. soorush. no.8:137-143. '59. (MIRA 12:12)

1.Chlen-korrespondent AN SSSR. (Structural frames—Vibration)



TO A THE THE ROTTING VIOLENCE CHECKER FOR THE PROPERTY OF THE

SNITKO, Nikolay Konstantinovich, prof., doktor tekhn.nauk; RABINOVICH, I.M., prof., doktor tekhn.nauk, retsenzent; FILIN, A.P., prof., doktor tekhn.nauk, nauchnyy red.; KAPLAN, M.Ya., red.izd-ve; VORONZTSKAYA, L.V., tekhn.red.

[Dynamics of structures] Dinamika scoruzhenii. Leningrad, Gos. izd-vo lit-ry po stroit., arkhit. i stroit.materialam, 1960.
355 p. (MIRA 13:7)

1. Chlen-korrespondent AN SSSR (for Rabinovich).
(Structures, Theory of) (Vibration)

RABINCVICH, Isaak Moiseyevich, ed.

Structural Mechanics in the U.S.S.R.; 1917-1957.

New York, London, Pergamon Press, 1960.

VIII, 431 p.

Translated from the Original Russian: Stroitel'naya

Mekhanika v SSSR, 1917-1957. Moscow, 1959.

Includes Bibliographies.

#### PHASE I BOOK EXPLOITATION

SOV/5481

Rabinovich, Isaak Moiseyevich, Corresponding Member, Academy of Sciences USER, Member of the Academy of Construction and Architecture of the USER,

Osnovy stroitel'noy mekhaniki stershnevykh sistem (Pendementals of the Structural Mechanics of Systems of Trusses) 3rd ed., rev. and enl. Moscov, Gosstroyizdat, 1960, 518 p. Errata slip inserted. 25,000 copies printed.

Ed. of Publishing House; E. M. Bedarina; Tech. Ed.: L. M. Osenko.

FURFORE: This book was authorized by the Ministry of Higher and Secondary
Specialized Education of the USSR (Ministerstve vysshego i srednego special'nogo obrasovaniya SSSR) as a textbook for students of structural engineering
vures and divisions in schools of higher education.

COVERAGE: The following subjects are covered: 1) Nethods for calculating statically determinate systems, including three-dimensional trasses; 2) methods for calculating statically indeterminate systems (continuous beems, frames, archos and trusses); 3) the fundamentals of stability calculations and calculations for dynamic loading effects; and 4) the fundamentals of approximate

Card 1/25-

Fundamentals of the Structural Mechanics (Cont.)

sov/5481

bulkhead calculations. Styeral sections that appeared in the second edition have been slightly enlarged. The chapter on the calculation of a beam on a continuous elastic base has been supplemented and many additions were made to the part on the dynamics of mechanisms. The author thanks the reviewers of the book: Kafedra stroitel'noy mekhaniki Kiyevskogo inzhenerno-stroitel'nogo instituta (Department of Structural Mechanics of the Kiyev Construction Engineering Institute) headed by Professor D. V. Vaynberg and Professors D. V. Bychov, G. K. Kleyn, and V. G. Rekach. A considerable number of Soviet, French, German, English, Italian, and Latin references appear at the end of some chapters and in footnotes to the text.

#### TABLE OF CONTENTS:

Author'	s Preface	
	Introduction	
	Scope and problems of structural mechanics Fundamentals of calculation schemes for mechanisms	
	Classification of calculation schemes for mechanisms Classification of supports of two-dimensional truss systems  19	
	그리다. 그리는 이 그렇게 되고 하여 되는 것이라면 하는 것 같은 말을 받아 다시가 한다.	
. 5	Kinematic Analysis of Mechanisms Degree of freedom of a two-dimensional kinematic chain	
Card 2/	consisting of disks	!
saru 2/	52 이 문학 사람들은 살이라는 학자가 있다면 하는 하는 학자를 하는 것 같아 하는 것 같아.	

Designing structure to the periodic law	. Isal. po	teor. sooruzh. no	ime according . 9:109-118 (MIRA 14:1)	
	Structures,	Theory of)		

是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就会一个人,我们就是一个人,我们就会这一个人,我们

MATEVOSYAN, Rafael! Rubenovich; RABINOVICH, I.M., prof., doktor tekhn.nauk, retsenzent; KHALAFYANTS, N.M., red.izd-va; EL'KINA, E.M., tekhn.red.

[Stability of composite red systems (qualitative theory)] Ustoichivost' slozhnykh sterzhnevykh sistem (kachestvennaia teoriia).
Moskva, Gos.izd-vo lit-ry po stroit.arkhit.i stroit. materialam,
1961. 251 p. (Akademiia stroitel'stva i arkhitektury SSSR. Institut
stroitel'nykh konstruktsii. Trudy, no.3). (MIRA 14:10)

1. Chlen-korrespondent AN SSSR i deystvitel'nyy chlen Akademii stroitel'stva i arkhitektury SSSR (for Rabinovich).

(Structures, Theory of)

#### "APPROVED FOR RELEASE: Tuesday, August 01, 2000

CIA-RDP86-00513R001343

EWP(r)/EWT(d)/EWT(m)/BDS L 17406-63 124/63/000/004/044/064

AUTHOR:

Rabinovich, I. M.

by the forms of natural oscillations

TITLE:

PERIODICAL: Referativnyy zhurnal, Mekhamika, no. 4, 1963, 19, abstract 4V147 (Stroit. mekhan. i raschet sooruzh., no. 4, 1961, 1-4)

TEXT: The author shows that upon analysis of a load by the forms of the natural oscillations of an elastic columnar system, there does not always exist a mutually single-valued correspondence between load and breakdown. To a given load corresponds one definite analysis; to the latter, however, may correspond an infinite number of loads, distinguished by loads of "zero" type - that is, loads whose work is equal to zero with any displacements of the system. Such loads may be included in a system having nondeformed elements. The author gives examples. F. M. Dimentberg.

[Abstracter's note: Complete translation.]

Card 1/1

1. Chlen-korrespondent AN SSSR. (Structures, Theory of)	Designing statically indeterminate systems with exce of contact on one side. Issl. po teor. sooruzh. no '61.	ssive points .10:163-169 (MIRA 14:8)
	1. Chlen-korrespondent AN SSSR. (Structures, Theory of)	
생물로 보고 있는 것이 되었다. 그는 그는 그는 그는 그를 보고 있는 것이 되었다. 그는 물로에 보고 바로 함께 되었다. 그들지, 그는 그는 그는 그는 것이 모르는 것이 되었다. 그는 그를 보고 있는 것이 되었다. 그는 것이 되었다. 그는 것이 되었다.		

1. Chlen-korrespondent AN SSSR. (Elasticity)		Dynamics of a bilinear elastic system with one degree of freedom.  Issl. po teor. sooruzh. no.10:38-45 '61. (MIRA 14:8)	
		1. Chlen-korrespondent AN SSSR.	
			ļ.

RABINOVICH, I.M., red.; BEGAK, B.A., red. izd-va; TEMKINA, Ye.L., tekhn. red.

[Suspension roofs; transactions] Visiachie rokrytiia; trudy. Pod red. I.M.Rabinovicha. Moskva, Gosstroiizdat, 1962. 247 p. (MIRA 15:7)

1. Soveshchaniye po issledovaniyu i vnedreniyu visyachikh pokrytiy, Moscow, 1961. 2. Deystvitel'nyy chlen Akademii stroitel'stva i arkhitektury SSSR i chlen-korrespondent Akademii nauk SSSR (for Rabinovich).

(Roofs, Suspension)

KUZ'MIN, N.L., kand. tekhn. nauk; REKACH, V.G., doktor tekhn. nauk; ROZENBLAT, G.I., kand. tekhn. nauk; RABINOVICH, I.M., red.; GORYACHEVA, T.V., red.izd-va; KOMAROVSKAYA, L.A., tekhn.red.

[Collection of problems for a course in structural mechanics; pt. I - Problems, Pt.II - Answers and solutions Sbornik zadach po kursu stroitel'noi mekhaniki; ch.I - Zadachi, ch.II - Otvety i resheniia. Pod red. I.M. Rabinovicha. Izd.2., perer. Moskva, Gosstroiizdat, 1962. 331 p. (MIRA 16:2)

1. Chlen-korrespondent Akademii nauk SSSR, deystvitel syy chlen Akademii skroitel stva i arkhitektury SSSR (for Rabinovich).

(Structures, Theory of)

L 16750-63

EWT(d)/EWT(1)/BDS AFFTC/ASD/IJP(0)

5/124/63/000/004/046/064

AUTHOR:

Rabinovich, I. M.

53

TITLE:

Linear oscillations of a complex columnar system with finite number of degrees of freedom and of oscillation of its elements

PERIODICAL:

Referativnyy zhurnal, Mekhanika, no. 4, 1963, 20, abstract 4V149 (Sb. Issled. po teorii sooruzh. vyp. 11, M., Gosstroyidat, 1962, 115-126)

TEXT: The author proposes a method for the study of natural oscillations of a system with finite number of degrees of freedom, with use of forced oscillations of a simpler system formed from the given one by breaking it down. In the author's presentation the idea consists of the fact that "the natural oscillations of a complex system are at the same time forced oscillations of its elements." The problem of determining the natural frequencies of the mechanical system in question is reduced by the author to determine the frequencies of a certain fictitious external exciting force of harmonic type applied to a simpler (unconnected) mechanical system. The author takes up a number of concrete examples which illustrate the use of his method. The method, as he points out, can be adapted to the study of the stability of complex elastic columnar systems; particularly to determining complex critical values of external loads. A. I. Oseled'ko.

Card 1/1 [Abstracter's note: Complete translation.]

PROTASOV, Konstantin Georgiyevich, doktor tekhn. nauk; RABINOVICH,
I.M., prof., retsenzent; KRYL'TSOV, Ye.I., kand. tekhn.nauk,
retsenzent; NEKLEPAYEVA, Z.A., inzh., red.; MEDVEDEVA, M.A.,
tekhn. red.

[New cable-supported trusses] Novye vantovye fermy. Moskva, Transsheldorizdat, 1963. 98 p. (MIRA 16:4)

1. Chlen-korrespondent Akademii nauk SSSR (for Rabinovich). (Trusses) (Bridges, Iron and steel)

Invariants of statically indeterminate systems and some applications of them. Issl. po teor. socrush. no.12:141-158 63.

(MIRA 16:6)

1. Chlen-korrespondent AN SSSR, deystvitel'nyy chlen Akademii stroitel'stva i arkhitektury SSSR. (Invariants)

# PARINOVICH, I.M. (Moskva)

end in the second of the secon

Invariants of statically indeterminate systems and some applications of them. Issl. po teor. socruzh, no.12:141-158 '63.

(MIRA 16:6)

1. Chlen-korrespondent AN SSSR, deystvitel'nyy chlen Akademii stroitel'stva i arkhitektury SSSR.

(Invariants)

GOL'DENBLAT, I.I.; KORENEV, B.G.; RABINOVICH, I.M.; SMIRNOV, A.F.

Concerning the article by A.A.Pikovskii and A.A.Derkachev,
"Dynamic theory of stability." Stroi.mekh.i rasch.soor. 5
no.2:44-47 '63. (Stability)

(Stability)

RABINGVI	CH,I.M. (Mo	escow)				
	" On the p	eroblem of mi	nimumweight	structural d	esign".	
	Report pre	esented at the	e 2nd All-Un Moscow 29 J	ion Congress an - 5 Feb 6	on Theoreti	cal

SMIRNOV, Anatoliy Filippovich, doktor tekhu. nauk, prof.;
ALEKSANDROV, Anatoliy Vasil'yevich; SHAPOSHNIKOV,
Nikolay Nikolayevich; LASHCHENIKOV, Boris Yakovlevich;
RABINOVICH, I.M., doktor tekhu. nauk, prof., retsenzent;
OSIPOVA, E.M., red.; ZUBKOVA, M.S., red.

[Calculating structures by using computing machines; a manual for colleges] Raschet socruzhenii s primeneniem vychislitel'nykh mashin; uchebnoe posobie dlia vuzov. [By] A.F.Smirnov i dr. Moskva, Stroiizdat, 1964. 379 p. (MIRA 18:2)

SHIGHOV, A.F., prof., red.; RABINOVICH, 1.M., prof., red.; SHIGHOV, A.F., prof., red.; LUZHIN, O.V., kend. tekhn. nauk, nauchn. red.

[Problems of stability in structural mechanics] Problemy ustoichivosti v stroitel'noi mekhanike; trudy. Moskva, Stroitedt, 1965. 474 p. (MIRA 18:5)

1. Vsesoyuznaya konferentsiya po problemam ustoychivosti v stroitel'noy mekhanike, Moskva, 1963.

ARKHANGEL'SKIY, F.K., inshener; TEREMETEV, A.S., inzhener; RABINOVICH, I.N., inshener; SHAPIRO, D.V., inshener.

Development of electric machinery construction at the Kirov "Elektrosila" Plant. Vest.elektroprom. 18 no.11:7-10 I '47. (MERA 6:12)

1. Zavod "Elektrosila" im. S.M.Kirova. (Electric machinery)

:	ARINO	ovicii,	I., N.												
	CHALIF Elektr	O, D. rosila,	V. and No. 5	PABINO	vicii, p. 52	1. N. 2-54.	"Neu	excit	ers for	synch	roncus	turbo	-vener	ators",	
	50: L	J-3042,	ll Ma	rch 53,	(Leto	pis '	Zhurnal	'nykh	Statey	, No.7	1949)	•			
															·
		e an e e egy.								a washing					4

RABINOVICH, IN.

ZIMIN, Vladimir Ivanovich; KAPLAN, Moisey Yakovlevich; PALEY, Anna
Markovna; RABINOVICH, Leay Betanovich; PEDOROV, Vasiliy Petrovich;
IHAILIN, Petr Andreysvich; RIVLIN, L.B., redaktor; VORONETSKAYA,
L.V., tekhnicheskiy redaktor.

[Windings of electric machinery] Obmotki elektricheskith mashin.
Izd. 4-e, perer. Moskva, Gos. energ. izd-vo, 1954. 575 p.

(Electric machinery)

(MEA 8:1)

AID P - 1470

THENCYCH, LM.

Subject : USSR/Electricity

Card 1/1 Pub. 27 - 21/36

Authors: Rabinovich, I. N., Bayko, V. F., Vavilov, A. A., Engs.

Title : Amplidyne regulators with in-phase field (Discussion of the article by O. I. Zolotarev, Elektichestvo, No.3,

1953)

Periodical: Elektrichestvo, 2, 67-68, F 1955

Abstract : The authors criticize the statement of the problem by


O. I. Zolotarev, in which they say he made several incorrect assumptions leading to wrong conclusions. They also criticize the definitions of the basic

characteristics of amplidyne regulators. This, they conclude, disqualifies the article for use in the study

and testing of this type of electrical machinery.

Institution: Plant "Elektrosila"

Submitted: No date



SOY/112-58-2-2185

Translation from: Referativnyy zhurnal, Elektrotekhnika, 1958, Nr 2, p 62 (USSR)

AUTHOR: Rabinovich, I. N.

TITLE: The Large DC Machines of the "Elektrosila" Plant im. S. M. Kirov (Krupnyye mashiny postoyannogo toka zavoda "Elektrosila" im. S. M. Kirova)

PERIODICAL: V sb.: Raboty M-va elektrotekhn. prom-sti SSSR po mekhaniz. i avtomatis. nar. kh-va. Z. M., 1956, pp 5-16

ABSTRACT: The "Elektrosila" plant builds large DC electric motors of 25-6,500 km with torque up to 120 tm and overload torque up to 300 tm. To supply power motors, the plant builds AC-DC motor generator sets in which individual generator capacity reaches 5,000 km. Over the last few years, a number of high-rom DC motors have been built that have a wide range of speed regulation, e.g.: 4,195 km, 150/300 rpm; 2,210 km, 360/720 rpm; 1,840 km, 200/400 rpm. These motor types have been built: motors for high-speed plate-rolling mills; motors with built-in air-filters intended for meteorological plants; motors for high-productivity shovels with 14-m bucket capacity; motors for high-speed

Card 1/2

SOY/112-58-2-2185

The Large DC Machines of the "Elektrosila" Plant im. S. M. Kirov

elevators, etc. The batch production of electrical equipment for Diesel electric ships of up to 10,000 tons has been organized. Machines with still higher capacities are being developed; e.g., 14,720 kw ship-propulsion motors. A single standardized line of large DC machines is being designed.

A.G.K.

Card 2/2

SOV/110-59-2-1/21

Ivanov, N.P., Pankratov, B.Ya., Rabinovich, I.N., and AUTHORS:

Engineers Shubov, I.G.,

Water-cooled Direct Current Machines (Mashiny TITLE:

postoyannogo toka s vodyanym okhlazhdeniyem)

PERIODICAL: Vestnik Blektrepromyshlennosti, 1959, Nr 2, pp 1-4

(USSR)

ABSTRACT: The disadvantages of normal methods of cooling rotating

machines are briefly described. Graphs showing the reduction in output for a given frame size for totally enclosed as compared with protected machines are given in Fig 1. The increase in overall machine size that results from the use of air coolers is illustrated by the outline drawings of Fig 2. Because of the great need for a small totally enclosed machine the authors have developed the design and manufacture of an enclosed machine with internal water cooling, a general view of which is given in Fig 3, whilst the armature and stator are shown separately in Fig 4. The machine is cooled by special elements in the form of brass discs to which brass tubes are brazed (see Fig 5A). These plates, which

are 10 mm thick, are assembled in the armature steel. Card 1/3

Water-Cooled Direct Current Machines SOV/110-59-2-1/21

The ends of the tubes are all connected to the central bore of the shaft, and at the free end of the shaft there is a water distributing head which has channels for delivery and return of water. The main and commutating poles are cooled by the flat brass elements illustrated in Figs 5b and 5c which also contain cooling tubes. The ends of all the tubes in the cooling elements of the stator are brought out to a water distributing ring. Comparative test data for this totally enclosed machine with and without water cooling and with a protected machine are tabulated, and it will be seen that the use of water cooling increases the output of the enclosed machine from 4 to 17 kW. The water consumption is about 15 litres/min and the inlet temperature is 1200. output of the protected machine is 14 kW. The first experimental machine did not make the best use of the

SOV/110-59-2-1/21

Water-Cooled Direct Current Machines

cooling facilities available and later designs are improved in this respect; there will be more coolers in the stator, the field windings will be made of hollow conductors and a pump will be built into the machine to make it more independent. The construction is particularly advantageous for machines with a wide range of operating speeds which normally require external fans. The main disadvantage of water cooled machines is that

Card 3/3 they need fresh water.

There are 5 figures and 1 table.

SUBMITTED: June 20, 1958

ZIMIN, Vladimir Ivanovich; KAPLAN, Moisey Yakovlevich; PALKY, Anna Markovna; RABINOVICH, Isay Natenovich; FEDOROV, Vasiliy Petrovich [deceased]; KHAKKEN, Petr Andreyevich; RIVLIN, L.B., red.; SOBOLEVA, Ye.M., tekhn.red. [Electric machinery windings] Obmotki elektricheskikh mashin.

Izd.5., perer. Moskva, Gos.energ.izd-vo, 1961. 475 p. (MIRA 14:6)

(Electric machinery-Windings)

1. Nachal'nik konstruktorskogo byuro zavoda "Elektrosila".  (Electric machineryDirect current)	Modern d.c. machines and problems of commutation. zav.; elektromekh. 5 no.10:1188-1194 62.	Izv.vys.ucheb. (MIRA 15:11)
	1. Nachal'nik konstruktorskogo byuro zavoda "Elektr (Electric machinery-Direct current)	osila".

RABINOVI					
	Present-day d.o no.22:3-8 '63.	. machines and	problems of c	omutation. Elektronic (MIRA 17:1)	rosila

EWT(1) L 18532-66

ACC NR. AP6002683

SOURCE CODE: UR/0292/66/000/001/0010/0013

AUTHOR: Rabinovich, I. N. (Engineer); Shubov, I. G. (Candidate of technical

ORG: none

sciences)

TITLE: Design of synchronous machines with claw-shaped rotors

SOURCE: Elektrotekhnika, no. 1, 1966, 10-13

TOPIC TAGS: synchronous machine, electric generator unit

ABSTRACT: Some hints are given for designing high-speed higher-frequency unwound-rotor synchronous generators intended for autonomous plants; they may have a capacity up to 1000 kw or more. The advantages and disadvantages of singleand multipacket stator construction are discussed. Water-cooled stators and aircooled rotors are recommended for higher-capacity machines. Criteria for Card 1/2

L 18532-66 CC NR: AP6002683

maximum parameters of the single-packet construction (flux density, stator loading) are formulated; also, recommendations are given for the spacing between packets in multipacket construction and for limiting the bearing currents. In addition to its primary function, the synchronous generator with a claw-shaped rotor can also develop a considerable amount of d-c low-voltage power; extraction of this power, however, requires overcoming some slip-contact design difficulties. Orig. art. has: 7 figures and 18 formulas.

SUB CODE: 09 / SUBM DATE: none / ORIG REF: 002 UDC: 621.313.32.001.24

16

2/2

RAYEVSKIY, N.P.; VLADIMIROV, B.V.; KCMAROV, N.S., red.; SHCHUCHKIN, N.V., red.; SOLOV'YEV, D.I., red.; RABINOVICH, I.P., red.; VASILENKO, I.F., red.; MODEL', B.I., tekhn. red.

[Theory, design, and manufacture of agricultural machinery] Teoriia, konstruktsiia i proizvodstvo sel'skokhoziaistvennykh mashin. Moskva, Gos. nauchno-tekhn. izd-vo mashinostroit. lit-ry. Vol.7. [Atlas of general agricultural machinery parts] Atlas obshchikh detalei sel'khoziaistvennykh mashin. 1945. 335 p.

(Agricultural machinery)

RABINOVICH, I.P. OMEL'YANOV, A.Ye.; RABINOVICH, I.P.; BOLKHOVITIMOV, W.F., doktor tekhnicheskikh nauk, Fetsenzent; KUNYAVSKIY, M.B., kandidat tekhnichicheskikh nauk, redaktor. [Reference manual on materials in farm machinery parts] Spravochnik po materialam detalei sel'skokhosiaistvennykh mashin. Isd. 2-e ispr. i dop. Moskva, Gos. nauchno-tekhn. isd-vo mashinostroitel'noi i sudostroitel'noi lit-ry, 1954. 527 p. (Agricultural machinery industry)

SOV/137-57-1-1002

Translation from: Referativnyy zhurnal. Metallurgiya, 1957, Nr 1, p 128 (USSR)

AUTHOR: Rabinovich, I. P.

TITLE: Wear of Farming-machinery Components and Means of Increasing

Their Wear Resistance (Iznos detaley sel'skokhozyaystvennykh

mashin i puti povysheniya ikh iznosostoykosti)

PERIODICAL: V sb.: Povysheniye dolgovechnosti mashin. Moscow, Mashgiz,

1956, pp 434-444

ABSTRACT: Farming-machinery components may be classified into the following

groups: 1) Components subjected to abrasion directly by the soil, e.g., plowshares, moldboards, and cultivator claws; 2) components subjected to wear by vegetable matter, such as blades, thresher bars, and teeth; 3) components suffering wear in regions of contact

with other surfaces in the presence of an abrasive interlayer: Enclosed gear trains, bearings (an abrasive interlayer is absent in that case), and bushings; exposed gears, and grate-type conveyors of potato-harvesting machines. Information on the abrasion of com-

ponents belonging to these groups is presented, and means of suppressing this effect are outlined. Plowshares made of carbon steel

Card 1/3

SOV/137-57-1-1002

Wear of Farming-machinery Components and Means of Increasing (cont.)

(L53, L65) suffer maximum wear during plowing of sandy soils containing large quantities of pebbles (particularly the dense soils of Uzbekistan); the blades of the plowshares are hardened locally to a width of 25-40 mm to achieve an HR value of 450-650 (any further increase in hardness reduces the wear only slightly). In regions of heavy soils (containing significant quantities of stones) the employment of plowshares with a local blade hardness of HB = 500-555 is advisable, provided the blades had not been overheated prior to tempering; in that instance, a blow impinging on the tip of the blade produces only bending of the latter. Selfsharpening of the plowshares is achieved by employing two-layer (bimetallic) blades (surfacing with stalinite or with sormite containing an addition of B, onesided surface hardening, or chrome plating). Employed on any type of soil, with the exception of sand and sandy loam, such plowshares require frequent repairs (although a sharp blade is produced, it is incapable of deep penetration since the cutting angle acquires a negative value). The conditions under which the blade operates were simulated on a special device described in the article. Best results were achieved with blades made of steel Khl2; compared with steels L53 and 65G, the steel 55S2 offers certain advantages. Wear resistance increases with increasing hardness; however, when Rc > 61, certain grades of steel exhibit a tendency toward reduced wear resistance. The presence of the two metal layers does not produce any essential changes in the nature of wear of the Card 2/3

SOV/137-57-1-1002

Wear of Farming-machinery Components and Means of Increasing (cont.)

blade and does not offer any advantages. High wear-resistant properties were exhibited by white cast iron (RC of 42-44); chrome-plated carbon-steel plowshares were found to be inferior to other types of plowshares tested. It is recommended that plowshares be designed in a manner permitting the employment of interchangeable parts; the employment of contaminated steel with a nonhomogeneous structure should be avoided if the heat-treatment procedures do not include overheating and decarburization. HF induction heating must be automatized. The lower hardness limit of plowshare blades must amount to  $H_{B}$ =500, the only exception being plowshares which are intended for operation on rocky soils; this latter type requires a lower hardness and a special reinforced construction. The zone of quench hardening should be broadened in the case of plowshares intended for sandy soils. Designs must be developed for interchangeable tips made of white cast iron or carbide steel. Recommendations are also given with regard to the design and heat treatment of moldboards (a three-layer steel blade is required), cultivator claws, segments, tooth gears, sprocket wheels, ratchets, bushings, bearings, and links of grate-type conveyors (a design must be developed which would prevent the penetration of abrasive particles into the machinery in the process of the segregation of potatoes from the soil; it is essential that the area of the contact surface be increased). A. M. Card 3/3

GAPANOVICH, A.A.; RABINOVICH, I.P. Impact tests for agricultural machinery parts. Sel'khosmashina no.11:27-29 # '56. 1. Vsesoyuznyy nauchno-issledovatel skiy institut sel'skokhosynystvennogo mashinostroyeniya. (Agricultural machinery-Testing) (Metals-Testing)

RABIMOVICH, I.P., kandidat tekhnicheskikh nauk.

Flame hardening; a survey. Sel'khozmashina no.8:31-33 Ag '57.
(MIRA 10:8)

1.Veesoyusny nauchno-issledovatel'skiy institut sel'skokhozyaystvennogo mashinostroyeniya.

(Metals-Hardening)

a language state of the		CONTROL HARMAN	15.000				t
	RABIL	NOVICH,	T, P	n neuk: NI	LOVSKIY, I.A.,	inzh.; ROZENBAUM,	A.N., Inzn.
	RABINOV	ICH, I.P., Increasing	kand text	wasistance	of plowshares	. Sel'khozmashina (MIRA 1	no.11:10-15 0:12)
	The second second	Increasing	the Wear	18810			
		N 157.			(Plows)		지 말 중에 되는 것이다. 전략 15 전략으로 하다
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						
than in the							
34 January			the street of				
		1 - 1					
						그는 역 이 이 모델 중대를 하고	
	ing and the second of the seco						
	Name (Inc.)						The second second second
				4 4 4			
	1 21 <u></u>		N 1				

Using new materials in manufacturing agricultural machinery.
Trakt.i sel'khozmash. 30 no.10:25-27 0 '60. (MIRA 13:9)

1. Vsesoyusnyy nauchno-issledovatel'skiy institut sel'skokhozyaystvennogo mashinostroyeniya.
(Agricultural machinery industry)

Use of Brinell	test. Trakt.	i selikhozmash	. 31	no.8:44-46	Ag (MIRA	'61. 14:7)
1. Vsesoyuznyy nogo mashinosti	oveniva.		institu	it sel'skokho	syays	tven-
		rinell test)				

RABINOVICH, I.P.; KOROTKOV, A.G.; DREVYATNIK, P.P.

Control of the mechanical properties of gray pig iron by a method which involves mixing with liquid steel. Trakt. i selkhozmash.

32 no.3:39-40 Mr '62. (MIRA 15:2)

(Cast iron--Metallurgy)

RABINOVICH, I.P., kand.tekhn.nauk; KLIMCHUK, Yu.F., inzh.

Use of plastic materials for increasing the reliability and operating life of agricultural machinery. Trakt. i sel'khozmash. 32 no.10:21-23 0 '62. (MIRA 15:9)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut sel'skokhozyaystvennogo mashinostroyeniya. (Agricultural machinery) (Plastics)

RABINOVICH, I.P., kand. tekhn. nauk; KIPNIS, S.B., inzh.

Increasing the service reliability and life span of welded constructions. Trakt. i sel'khozmash. 33 no.3:38-41 Mr. 163.

(MIRA 16:11)

1. Vsesoyuznyy nauchno-issledovatel skiy institut sel'skokhozyaystvennogo mashinostroyeniya.


KLETSKIN, M.I.; RABINOVICH, I.P., kand. tekhn. nauk; TEMENBAUM, M.M., kand. tekhn. nauk

The second of the second property of the second sec

Estimating the reliability and life of agricultural machines.

Trakt. i sel'khozmash. 33 no.5:1-4 My '63. (MIRA 16:10)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut sel'skokhozyayst-vennogo mashinostroyeniya. 2. Glavnyy konstruktor Vsesoyuznogo nauchno-issledovatel'skogo instituta sel'skokhozyaystvennogo mashinostroyeniya (for Kletskin).



Chromatographic methods used at the Saratov Plant of Alcohol. Zav.lab. 28 no.5:636-637 162.	(MIRA 15:6)
<ol> <li>Saratovskiy zavod sinteticheskogo spirta.</li> <li>(Saratov—Alcohol) (Chromatographic analysis</li> </ol>	1948년 - 1947년 (1948년 1947년 ) 1948년 - 1947년 - 1948년 (1947년 ) 1947년 - 1947년 (1947년 )
	현실 기계 기계 현실 선택을 받았다. 

L 15688-65 EWT(d) Po-4/Pq-4/Pg-4/Pk-4/P1-4 ASD-3/AFFTC/ESD-3/APGC ACCESSION NR: AP4047481 S/0120/64/000/005/0157/0161

AUTHOR: Levina, L. Ye.; Men'shikov, M. I.; Pavlenko, V. A.; Rabinovich, I. S. Rafal'son, A. E.; Tsy\*mberov, M. Ya.; Shutov, M. D.

TITLE: New MKh 1101 mass-spectrometric leak detector

SOURCE: Pribory\* i tekhnika eksperimenta/ño. 5, 1964, 157-161

TOPIC TAGS: leak detector, mass spectrometric leak detector / MKh 1101 leak detector

ABSTRACT: The new MKh 1101 leak detector differs from previous types (PTI-4a and PTI-6) in that it has no oil-vapor pump, uses an oxidation-resistant cathode, and is calibrated by a reference diffusion-type helium leak. Two lobar rotary (Roots) pumps driven by a single motor provide the rough and fine vacuums: the equilibrium vacuum is (2-5) x 10<sup>-4</sup> torr. The cathode is stable in

operation at pressures up to 1 torr. The leak detector sensitivity is (1-5) x 10-

Card 1/2

L 15688-65

ACCESSION NR: AP4047481

lmc/sec for helium and  $5 \times 10^{-4}$  lms/sec for hydrogen. Setting the detector in operation takes only 10 minutes. Orig. art. has: 6 figures.

ASSOCIATION: SKB Analiticheskogo priborostroyeniya AN SSSR (Special Design Office for Analytical Instruments, AN SSSR)

SUBMITTED: 03Jun63

ENCL: 00

SUB CODE:ME

NO REF SOV: 002

OTHER: 000

APPROVED FOR RELEASE: Tuesday, August 01, 2000

CIA-RDP86-00513RD0134

**Card** 2/2

SOV/24-58-10-26/34

AUTHOR: Rabinovich, I. Sh. (Leningrad)

Towards a Solution of the Problem of Contact Between Cylinders with Parallel Axes (K resheniyu zadachi o kontakte tsil-TITLE: indrov s parallel'nymi osyami)

PERIODICAL: Izvestiya Akademii nauk SSSR, Otdeleniye tekhnicheskikh nauk, 1958, Nr 10, pp 139-140 (USSR)

The first solution of the Hertz problem for the case of central compression of two isotropic smooth cylinders with ABSTRACT: parallel axes was obtained by Ac. A. N. Dinnik. Dinnik used the general theory of Hertz (Ref.2) and obtained an expression for the area of contact of the cylinders, an elliptical law of distribution of pressure across the width of the contact and an infinite value for the change in the distance between the centres of the cylinders. The latter result is in disagreement with the physical aspect of the phenomenon and so Dinnik tried to find this change by a different method. He succeeded in solving the problem, but only in the special case of cylinders of the same radius and material and his result was

Card 1/3

SOV/24-58-10-26/34

Towards a Solution of the Problem of Contact Between Cylinders with Parallel Axes

confirmed experimentally. Belyayev later solved the Hertz problem for cylinders by a method which differs from that used by Dinnik (Ref.4). His expressions for the width of the area of contact and the law of distribution of pressures concide with those obtained by Dinnik. However, Belyayev's solution does not answer the problem of what is the change in the distance between the axes. The present author has re-examined Belyayev's paper and found that a constant of re-examined Belyayev's solution does not solve the above probfact that Belyayev's solution does not solve the above probfact that Belyayev's solution does not solve the change in lem. To an engineer it is important to know the change in the distance between the centres of the cylinders on compression. If the above constant of integration is taken into account, the present author finds that:

$$\alpha = p(\mathbf{J}_{1} + \mathbf{J}_{2}) \ln \frac{R_{1} + R_{2}}{R_{1}R_{2}(\mathbf{J}_{1} + \mathbf{J}_{2})p} + 2p(\mathbf{J}_{1} \ln R_{1} + \mathbf{J}_{2} \ln R_{2}) - \frac{\mathbf{J}_{1}\sigma_{1}}{1 - \sigma_{1}} + \frac{\mathbf{J}_{2}\sigma_{2}}{1 - \sigma_{2}},$$
(6)

SOV/24-58-10-26/34

Towards a Solution of the Prob m of Contact Between Cylinders with Parallel Axes

where  $R_1$  and  $R_2$  are the radii of curvature of the contacting cylinders,  $\mathcal{N} = (1 - \sigma^2)/\mathcal{N}E$ ,  $\sigma$  and E being the Poisson's and Young's moduli, and  $\rho$  is the compression load Poisson's are formulae given by Dinnik (Ref.1) and Foppl (Ref.3) approximate formulae given by Dinnik (Ref.1) and Foppl (Ref.3) in the special case where the radii of the cylinders are equal. There is 1 figure and there are 5 references; 3 of the references are Soviet and 2 are German.

SUBMITTED: October 28, 1957.

Card 3/3

27142 \$/121/61/000/004/002/008 D040/D113

1 1100

AUTHORS: Blokh, O. I., Rabinovich, I. Sh., and Rashkovich, M. P.

TITLE:

Magnetostrictive setting-up and feeding drive for precision

machine tools

PERIODICAL: Stanki i instrument, no. 4, 1961, 12-13

TEXT: Design and operation is described of a magnetostrictive drive suitable for micro-feed in grinders, for setting tools in diamond boring machines, and for accurate positioning of various precision machine tool mechanisms. The device ensures a pulse frequency of up to 10 per sec and feed variations from 1 to 10  $\mu$  for a base of 100 mm, whilst the existing drives of this kind produce a maximum of 1 cycle per sec (Ref. 1: L. S. Akhmechet, O. I. Blokh, V. S. Shorgin, "Stanki i instrument", No. 1, 1960; Ref. 2: J. G. Robinson, G. S. Butterworth, "Electrical Manufacturing", 1957). The drive (Fig. 1) has a rod (1) of "K-64" cobalt alloy increasing its length 90 microns per 1 meter in saturated magnetic field of a coil (2), and two hydraulic membrane clamps (3) (right and left) switching on in sequence. When the system is connected to a d.c. source, the rod portion between the

Card 1/4

271/2 S/121/61/000/004/002/008 D040/D113

Magnetostrictive setting-up ....

clamps magnetizes and elongates toward the released right clamp giving a push to the servo element (4) of the machine tool. The displacement magnitude depends on the length L of the rod and the saturation of magnetic field. The right clamp closes after the rod is elongated, and the left opens and the coil winding switches off. The rod contracts to initial length, the clamps assume zero position, and the cycle repeats. A nonadjustable radialpiston hydraulic pump (Fig. 2) controls the clamps. It has two cams in different planes, one controlling two 10 mm diameter pistons (di) and the other two 12 mm pistons  $(d_2)$ . Each  $d_1$  piston is coupled with a  $d_2$ , and the two piston couples are at a 450 angle to each other. Each pistons couple is a separate pump of 0.5 liter/min capacity at 300 rpm shaft velocity and controls one clamp. The description includes the control circuit diagram of the system, a separate diagram showing the design of the magnetic switch with an oscillating sector-shaped core, and an oscillogram of the system operation. There are 5 figures and 2 references: 1 Soviet and 1 non-Soviet bloc. The reference to the English-language publication reads as follows: J. G. Robinson, G. S. Butterworth, "Electrical Manufacturing", 1957.

Card 2/4

MATSIYEVSKIY, Anatoliy Gavrilovich; ERLIKH, Lazar Borisovich; Prinimali uchastiye: SLEZINGER, I.N., kand.tekhn.nauk, dots.; MENAKER, L.S., inzh.; RABINOVICH, I.Sh., inzh.; SVIRIDENKO, S.Kh., red.; ORLIKOV, M.L., dots., retsenzent; BYKOVSKIY, A.I., inzh., red.; GORNOSTAYPOL'SKAYA, M.S., tekhn. red.

[Efficient organization of machine-tool design] Ratsionalizatsiia raschetov pri konstruirovanii stankov. Pod red. S.Kh.Sviridenko. Moskva, Mashgiz, 1962. 127 p. (MIRA 15:7)


(Machine tools-Design)


RABINOVICH, I.Sh., inzh.; TETEL'BOYM, B.M., inzh.

Determining parameters of the driving-wheel profile of centerless grinding machines. Vest.mashinostr. 42 no.6167-69 Je '62. (MIRA 15:6)

(Grinding machines)

Once more about the solution of the contact problem for cylinders with parallel axes. Trudy GPI 18 no.4:91-94 '63.  (MIRA 17:9)		I. Sh., inzh.					
	Α	e more about the h parallel axes.	solution of t Trudy GPI 18	ne contact pr no.4:91-94	oblem for 63.	cylindera MIRA 17:9	3 )





#### "APPROVED FOR RELEASE: Tuesday, August 01, 2000

THE RESTRICT OF THE PROPERTY O

CIA-RDP86-00513R001343

ACC NR: AT6021749 (A) SOURCE CODE: UR/0000/66/000/000/0220/0222

AUTHOR: Rabinovich, I. Sh.

ORG: none

TITLE: The natural oscillation frequency of the float in a flowmeter

SOURCE: AN SSSR. Institut avtomatiki i telemekhaniki. Pnevmoavtomatika (Pneumatic automation). Moscow, Izd-vo Nauka, 1966, 220-222


TOPIC TAGS: pneumatic device, pneumatic control system, gas flow, flow detection, flow measurement, flow velocity

ABSTRACT: Float type flowmeters, in addition to the measuring gas and liquid flow, are finding increasing application in automatic control, where they are used to measure dimensions. The response speed in these applications has to be high and it is important to know the natural oscillation frequency of the float to prevent errors. The natural oscillation frequency of a float in the flowmeter shown in Fig. 1 is derived to the first order of approximation using a numerical solution method for the nonlinear differential equation expressing the motion of the float. At balance this equation is

 $\xi' + \frac{\pi K_{pd}}{\Omega} \xi = 0. \tag{1}$ 

where K is the taper inside the tube, containing the float, g is the gravitational

**Card** 1/2



S/081/62/000/010/010/085 3158/3144

AUTHORS:

Kikolayev, P. N., Rabinovich, I. V.

TITLE:

Thermochemistry of isotopic compounds. 1. The effect of substitution of deuterium for hydrogen on the heat capacity

of penzene

PERIODICAL:

Referativnyy zhurnal. Khimiya, no. 10, 1962, 44, abstract 10B268 (Tr. po khimii i khim. tekhnol., (Gor'kiy), no. 2,

1961, 242-250)

TEXT: The values of c<sub>p</sub> of liquid C<sub>6</sub>H<sub>6</sub> (I) and C<sub>6</sub>D<sub>6</sub> (II) were measured in the temperature range 10-30°C. Values of c<sub>v</sub> for these compounds were calculated using data obtained previously on the contractability and coefficient of heat expansion of I and II (RZhKhim, no. 4, 1959, 10921; coefficient of heat expansion of I and II (RZhKhim, no. 4, 1959, 10921; no. 18, 1960, 76353). Complete substitution of deuterium for hydrogen no. 18, 1960, 76353). Complete substitution of deuterium for hydrogen caused an increase in the c<sub>p</sub> value of benzene by 13-14%, and in that of c<sub>v</sub> by 18-20 %. The ratio of c<sub>p</sub>:c<sub>v</sub> for I and II was 1.45-1.41 and

Card 1/2

Thermochemistry of isotopic...

S/081/62/000/010/010/085
B158/B144

1.37-1.34, respectively. The procedure and apparatus for measurement of are described as well as the procedure for preparation of II.

[Abstracter's note: Complete translation.]

OVICH, I.V.		
STRUCTURE AND PHYSICAL PROPERTIES OF MATTER IN A LIQUID STATE reports read at the 1th Conference convened in KIYEV from 1 to 5 Jun 1959, published by the publisheir House of KIYEV University, KIYEV, USSR, 1962		
Proface M.I. SHAKIPAROHCV, Dielectric Permeability and Molecular Atructure of Solutions	3 (16)	
S.F. VUK., On the Connection Between the Botary Mobility of Molecules and Viscosity of Molecules and Viscosity P.S. PEUR and 1.1. FABILISKIY, Fine Structure of the Colecular Light Scatter Line and the	, n	
Properation of Witras and in Liquida 1.V. MAKOV, Effect of Intermolecular Interaction on the Line width of the Combination-Scatter	15 20	
G.P. MOSHCHINA, 4.S. KAUHOVA. I.D. BUHUYEVA and T.G. POFLAVATSI Light-Scatter Investigation of the Fluctuations in Alcohol-aqueous and	KAYA.	
1.V. LABINOVICH, lastope Effect in the Viscosity of Deutero-	25 32	
Y.3. BAKHGHIYEV and M.5. APCHMIT, Spectroscopic Investiga- tion of the Internal Field in Solutions A.F. SKATSHEVSKIY, V.F. KLOCHKOV and YU.V. PASSOHNIE, Econtgenographic Investigation of the	45	
Structure of Some Liquid Silicon- organic Compounds	50	

181T7C RABINOVICH I. YA. Dec 50 USSR/Metals - Welding, Equipment "Combined Welding Transformer-Regulator (STN) of the Academician V. P. Nikitin System," I. Ya. Rabinovich, Cand Tech Sci, Sec of Elec Welding and Electrothermics, Acad Sci USSR "Avtogen Delo" No 12, pp 1-5 Claims USSR priority in using ac for elec arc welding and describes combined single unit welding transformer patented in 1927 by V. P. Mikitin. States that many foreign firms borrowed Soviet ideas and design of welding equipment. Specifically mentions Westinghouse and Allis-Chalmers which make transformers on the STN system. 181770

RABINOVICH, I. Ya.

Electric Welding

Developing work for the great communist construction projects in all branches. Avtog. delo, 23, No. 6, 1952.

9. Monthly List of Russian Accessions, Library of Congress, October 19582 Uncl.

CIA-RDP86-00513R001343

RABINOVICH I. YA.

Rabinovich I. Ya., "Static Characteristics and Their Application for the Analysis and Classification of Arc-welding Automatic Regulation Systems," Traktaty Sektsii po nauchnoy razrabotke problem elektrosvarki slektrotermii, No 1, Moscow, USSR Academy of Sciences, 1953, Pages 10-30; bibliography, 8 items.

Problems of the theory of automatic regulation of the Trudy Sekts.po nauch.rasrab.probl.elektrosv. i elektro	(MIMA 0:91
[153•] [[] [] [] [] [] [] [] [] [] [] [] [] [	(Electric welding)

ii — Sansasa		-
	RABINOVICH, I.Ya.	
	Static characteristics and their application in the analysis and classification of methods of automatic regulation of arc welding. Trudy Sekts. po tion of methods of automatic regulation of arc welding. Trudy Sekts. po tion of methods of automatic regulation of arc welding. Trudy Sekts. po tion of methods of automatic regulation at SSSR no.1:10 '53. nauch. rasrab. probl. elektrosv. i elektroterm. AN SSSR no.1:10 '53. (MERA 6:9)	
	(Blectric welding)	٠.
		. : - ]
	이 보는 하고 있다. 그는 말이 되는 것 같은 것은 하는 하는 것이 없다. 그리는 학생은 생활했다.	141
	일이 되는 이번에 하는 것이 되는 것이 되는 것이 되었다. 그는 그 사람들은 그리를 통해 다	
	요하는 사람들이 있는 것이 되었다. 이 사람들은 사람들이 되었다는 사람들이 되었다는 것이 되었다. 그런 사람들은 사람들은 사람들은 사람들은 사람들이 되었다. 사람들이 되었다는 것이 되었다면 하는 것이 되었다. 사람들은 사람들은 사람들은 사람들은 사람들은 사람들은 사람들은 사람들은	
	발발되는 [2] 1	яij

- 1. RABINOVICH, I. Ya.
- 2. USSR (600)
- 4. Inventors
- 7. Nikolai Nikolaevich Benardos. A. S. Ogiyevetskiy, L. D. Radunskiy. Reviewed by I. Ya. Rabinovich. Sov. kniga No. 3, 1953.

9. Monthly List of Russian Accessions, Library of Congress, June 1953, Uncl.

PABLEOVICH, Isask Yakoylevich, kandidat tekhnicheskikh nauk; TSEGEL'SKII,

V.Le, inshener, redakter; HEGAK, B.A., redakter; MEDVELEY, L.Ya.,

tekhnicheskiy redakter.

[Use of welding transfermers in construction work] Primensaie svarochnykh transformatorov v stroitel'stva. Moskva, Gos.isd-ve lit-ry
pe stroitel'stvu i arkhitekture, 1954, 48 p.

(Electric transformers) (Electric welding)

# RABINOVICH, I.Ya. [Use of welding transformers in construction work] Primenente syarochnykh transformatorov v stroitel'stve. Moskva, Gos. izd. lit. po stroitel'stvu i arkhitekture, 1954. 51 p. (MLRA 8:2D)

# RABINOVICH, I.Ya. Shortcomings of the rules for the design of electrotechnical apparatus for electric welding. Avtom. svar. 7 no.6(39):77-79 N-D 154. 1. Otdel svarki Instituta metallurgii Akademii nauk USSA. (Electric welding)

		ndidat tekhnicheskikh na		Vest.AN	SSSE	
	New principle of 25 no.8:53-55	of automatic three-phase	FLC AGIGIUE.	(MIRA	9:1)	
	25 NO.0.77-77	(Electric welding)				
		보통 함께 없고 조면 뭐라죠? 그리				
		가는 사람들이 많이 되었다. 				
ana diwasa						

NIKITIN, Vasiliy Petrovich, akademik; RABINOVICH, I.Ya., kandidat tekhnicheskikh nauk, otvetstvennyy redaktor; GRIGOR YEV, Ye.N., redaktor izdatel stva; SIMKINA, Ye.N., tekhnicheskiy redaktor; KASHINA, P.S., tekhnicheskiy redaktor

[Principles of a theory of transformers and generators for arc welding] Osnovy teorii transformatorov i generatorov dlia dugovoi svarki. Moskva, Izd-vo Akademii nauk SSSR, 1956. 237 p. (MLRA 9:11) (Electric welding)

Separation of the Company of the Com

EASTERNAE, G. M. and MADIMOVICH, I. Ma. (Caulidates of Technical Sciences) and SLEWUSHKINA, Ye. 1. (Engr.)

"Direct Current Power Sources with Universal Characteristics for Arc Welding."

paper presented at All-Union Scientific-Technical Conference on Welding in Shielding Gases, LEningrad, Dec 1957.

(Svarochnoye Proizvodstvo, 1958, No. 4, pp 46-47 - author Tyul'kov, M. D.)

RABINOVICH, I 44

135-4-4/15

SUBJECT:

USSR/Welding

AUTHOR:

Rabinovich, I.Ya., Candidate of Technical Sciences.

TITLE:

Some Peculiarities of the Work of Electrical Welding Equipment in Shielding Gas-Medium (Nekotorye osobennosti raboty elekto-oborudovaniya dlya avtomaticheskoy svarki v srede zashchitnykh

gazov).

"Svarochnoye Proizvodstvo", 1957, # 4, pp 12-15 (USSR)

ABSTRACT:

PERIODICAL:

A general review of the electro-technology of welding in shielding gases contains the following conclusions:

- 1) Feed sources of a rigid or a rising outer characteristic may be used for feeding a d.c. arc of a rising static characteristic.
- 2) For automatic welding in neutral gases particularly with a short arc fast-operating control systems must be applied. The intensity of arc self-controlling is, with the arc of a rising statical characteristic, considerably lower than with arc welding under flux, the other conditions being equal. When feeding from sources of a falling outer characteristic, the intensity of self-controlling can prove insufficient to obtain a stable process. In this case systems of forced voltage

Card 1/2

135-4-4/15

TITLE:

Some Peculiarities of the Work of Electrical Welding Equipment in Shielding Gas-Medium. (Nekotorye osobennosti raboty elektooborudovaniya dlya avtomaticheskoy svarki v srede zashchitnykh gazov).

control are to be applied.

3) The use of feed sources of a rigid or rising outer characteristic leads to a considerably more intensive self-control. 4) In order to reduce the possible disturbances in the speed of welding rod feed, it is advisable to use a drive of a rigid mechanical characteristic for the self-regulation systems of the arc.

The article contains 4 diagrams (electrical characteristics) and 1 table.

ASSOCIATION: Laboratoriya elektricheskikh svarochnykh mashin AN SSSR (Electrical Welding Machine Laboratory Academy of Sciences, USSR).

PRESENTED BY:

SUBMITTED:

AVAILABLE:

At the Library of Congress

Card 2/2

PHASE I BOOK EXPLOITATION

1091

### Rabinovich, Isaak Yakovlevich

- Oborudovaniye dlya dugovoy elektricheskoy svarki; istochniki pitaniya dugi (Equipment for Electric Arc Welding; Arc Power Supply Sources) Moscow, Mashgiz, 1958. 380 p. 13,000 copies printed.
- Reviewer: Bratkova, O.N., Candidate of Technical Sciences; Ed.:
  Shchitova, V.M., Candidate of Technical Sciences; Ed. of Publishing
  House: Stepanchenko, N.S.; Tech. Ed.: Model', B.I.; Managing Ed.
  for Literature on Heavy Machine Building (Mashgiz): Golovin, S.Ya.,
  Engineer.
- PURPOSE: This is a textbook for students in machine-building and polytechnic vuzes and covers a course in power supply sources for electric arc welding. It may also aid engineering and technical personnel concerned with arc welding in the selection and proper operation of electric welding equipment.
- COVERAGE: The material presented in the book is divided into four parts.

  The first part discusses the characteristics and properties of the

Card 1/12

Equipment for Electric Arc Welding (Cont.) 1091

rient vot franklingen milikeromen internolusionen komplektionen beskriver beskriver beskriver beskriver beskri

welding are and explains what requirements are imposed on the powergenerating equipment. The next two parts deal with the theory of operation and with basic properties and design characteristics of typical Soviet and non-Soviet power equipment used in manual and automatic a-c and d-c arc welding. The last part concerns the basic rules governing the construction and operation of electric arc welding units. In preparing this book the author utilized material submitted by many outstanding plants and research institutions concerned with welding such as the "Elektrik" Plant, VNIIESO, the USSR Academy of Sciences, the Institut elektrosvarki, AN, USSR (Institute of Electric Arc Welding, Academy of Sciences, Ukranian SSR), the MVTU imeni Baumana, TsNIITMASh, NIAT, the Ural'skiy politekhnicheskiy institut (Ural Polytechnic Institute), the Leningradskiy politekinicheskiy institut (Leningrad Polytechnic Institute) and others, as well as the results of his own research. Certain theoretical problems dealing with the theory of power supply for arc welding and presented in Chapter III (Sections 2,3,4), Chapters VIII, X, XIII, XIV and others, are the author's original contributions in this field or his further development of problems raised by other scientists. There are 53 Soviet references.

Card 2/12

MADE 17	OF COMMENTS		
TABLE	OF CONTENTS:		
Prefac			
Introd	duction. A Short Outline of the Develop Equipment for Arc Welding	oment of Electric	
	PART 1. CHARACTERISTICS OF THE WELDING FOR SOURCES OF ARC WELDING	NG ARC AND REQUIREMENTS POWER SUPPLY	
Ch. I 1. 2. 3.		es of arc welding	1 1 2
Ch. I		TGB OI OHE G-C GIO	3 3 3
	3/12		

3.	Characteristics of an a-c arc in a circuit containing resistance	43
4.	Characteristics of an a-c arc in a circuit containing in-	46
5.	ductance A three-phase welding arc	51
Ch. II	I. Stability of the Welding Arc and Static and Dynamic Properties Required of Power Sources	56
1.	Static stability of a system consisting of power source	5 <del>(</del>
2.	Stability of the arc and welding regime with changing arc	6:
3.	Static characteristics of are control systems and opera-	66
4.	Requirements imposed on the shape of external characteristics and the basic principle of the operation of power	7
5.	sources Dynamic properties of arc power supply	7
	그 시간 최고 본 등 보고 있는 시민 회 및 그 시민의 골반 시 로그램	
Card 4	<b>/12</b> [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ]	

Power Sources for Arc Welding  1. Basic types of power sources and their engineering character— 83 1stics 2. Setting the welding regime  PART 2. A-C POWER SUPPLY SOURCES  Ch. V. Principles of the Theory of Operation of Single-phase Welding Transformers 1. Basic equations and vector diagrams for transformers 2. Transformer equivalent circuits 3. Basic equations representing the operation of welding trans-
PART 2. A-C POWER SUPPLY SOURCES  Ch. V. Principles of the Theory of Operation of Single-phase Welding Transformers  1. Basic equations and vector diagrams for transformers  1. Basic equations and vector diagrams for transformers
Ch. V. Principles of the Theory of Operation of Single-phase Welding Transformers  1. Basic equations and vector diagrams for transformers  1. Basic equations are already to the standard of
Welding Transformers  1. Basic equations and vector diagrams for transformers  101
formers 4. Control of current and voltage in welding transformers 5. Classification of electromagnetic circuits of welding
transformers  Ch. VI. Transformer Circuits Having Normal Magnetic Leakage and Containing a Type STN Reactance Coil

<ol> <li>Control of operating regime</li> <li>Design of type STN transformers and their varieties</li> <li>Automatic control of high-power welding transformers</li> </ol>	118 126 132 143
Ch. VII. Transformers With Separate Reactance Choke Coil 1. Transformer electromagnetic circuit 2. Basic relationships 3. Control of the operating regime 4. Design of type STE welding transformers	149 149 150 151 152
Ch. VIII. Transformers With Increased Magnetic Leakage and Reactance Coll	157
<ol> <li>Electromagnetic circuit of a transformer with a movable magnetic core</li> </ol>	157
<ol> <li>Basic relationships in a transformer with an increased mag metic leakage</li> <li>Control of the operating conditions of transformers with</li> </ol>	- 159
movable magnetic cores Card 6/12	167

4.	Construction of welding transformers with a movable type	170
5.	STAN core Transformers with increased magnetic leakage and movable windings	172
	. Multiple Welding Station Transformers	182
1.	Basic characteristics of a multiple welding source.	182
2.	The state of the s	184
	Special Transformers and Power Supply Circuits for Three- phase and Two-phase Arc Welding	187
1.	Basic relationships in a circuit containing a times phase	188
2.	Principles of automation and methods of controlling one	192
3.	Three-phase arc power supply circuits and special three- phase welding transformers	199
4.	A type ST-2D transformer	204

<ol> <li>PS-100 welding coverter</li> <li>Oscillators and pulse generators for re-igniting the arc</li> </ol>	208 208 212
PART 3. D-C POWER SUPPLY SOURCES-WELDING GENERATORS AND RECTIFY UNITS	ING
Ch. XII. Fundamentals of the Theory of Operation of Generators  1. Basic principle of operation and typical varieties of	223
welding generator circuits 2. Elementary circuit of a welding generator with separate	223
excitation and demagnetizing series coil	226
3. Basic equations for welding generator operation 4. Control of operating regime	227
4. Control of operating regime 5. Construction and circuits of welding generators with sepa-	
rate excitation and demagnetizing series coil	233
6. Basic properties of welding generators with separate excitation and demagnetizing series coil	244

Equipment for Electric Arc Welding (Cont.) 1091	
Ch. XIII. Fundamentals of the Theory of Transients in D-C Welding	247
Generators  1. Transients in welding generators and methods of analyzing	247
them 2. Analysis of welding generator transients caused by arc voltage disturbance	251
3. Analysis of the processes occurring during of the generator	257
4. Analysis of the processes during transition	263
5. Methods of improving dynamic characteristics of welding generators	268
Ch. XIV. Welding Generators With a Magnetizing Parallel-connected ed Field Winding and a Demagnetizing Series-connected Field Winding  1. Elementary circuit of the generator	271 271 272
2. Basic equations of the operation of the wording gone	277
3. Control of operating regime 4. Construction and circuits of welding generators with magnetizing parallel-connected and demagnetizing series-connected field windings	279
Card 9/12	

Equipment for Electric Arc Welding (Cont.) 1091	
5. SMP-3 generator and welding unit 6. Basic properties of the generators	287 289
Ch. XV. Split-pole Welding Generators  1. Elementary circuit of the generator 2. Basic equations for operation of the welding generator 3. Control of the operating regime 4. Construction and circuits of split-pole welding generators 5. Basic properties of split-pole generators	291 291 293 297 300 307
Ch. XVI. Cross-field Welding Generators  1. Elementary electromagnetic circuit of the generator  2. Basic equations for operation of a cross-field generator  3. Construction of cross-field generators and methods of controlling their operating conditions  4. Basic properties of cross-field generators and some characteristics of transients	- 325
Ch. XVII. Multiple Welding Station Generators  1. Electric circuit and the principle of operation of a multiple welding station generator	329 329
Card 10/12	

uipment for Electric Arc Welding (Cont.) 1091  2. Basic properties of multiple welding station d-c units	331
2. Basic properties of multiple welding station con- 3. Construction and circuits of multiple welding station con- verters and plants	333
그 이번 이번 그림과 하는 전기를 다 된 요구요요요요 이번 모든 어떤 것을 받는다.	337
a principle of operation and proportion	337
of semiconductor rectifiers	341
2. Construction and circuits of rectified welding 3. Basic properties of rectifier units for welding	348
PART 4. BASIC RULES FOR ARRANGING AND OPERATING ELECTRIC ARC WELDING UNITS	CAL
Person Supply IIn1ts	352
h. XIX. Parallel Operation of Power Supply Units 1. General rules for connection. Distribution of load curren	t 352
1. General rules for connections transformers	355 356
	350
	360
h. XX. Selection and Assembly of Power Supply Units	360
1. Selection of the type of current 2. Selection of a power supply system for welding stations	361

但实现,1000年代,1000年代的1997年代,1997年代,1997年代,1997年代,1997年代,1997年代,1997年代,1997年代,1997年代		
Equipment for Electrical Arc Welding (Cont.) 1091		
3. Selection of the type of power supply unit 4. Selection of a power supply unit according to power rating 5. Location and installation of power units 6. Wiring of the power distribution network and the welding stations	362 362 363 364	
Ch. XXI. Basic Rules of Operation and Safety	368	
1. Average power factor of a welding-snop power supply and method of raising it	368 370	
3. Basic power supply troubles and methods for eliminating them 4. Basic safety rules	371 372	
Literature	375	
AVAILABLE: Library of Congress		
GO/sfm 2-18-59		
Card 12/12		

Rubidedien, I. Y.

AUTHORS:

Shchitova, V.M. and Rabinovich, I.Ya.

125-1-7/15

TITLE:

Problems of the Dynamics of D.C. Power Sources for Automatic Shielded-arc Welding (Voprosy dinamiki istochnika pitaniya pri avtomaticheskoy svarke v zashchitnykh gazakh)

PERIODICAL:

Avtomaticheskaya Svarka, 1958, # 1, pp 43 - 47 (USSR)

ABSTRACT:

Experimental and theoretical investigations carried out in the laboratory of electric welding machines of the USSR Academy of Sciences, show that the choice of circuits and shapes of the external characteristics of D.C. power sources must correspond to their dynamic properties. The following questions are outstanding in an analysis of the dynamics of a system consisting of a power source and an arc: 1) the investigation of transition processes in the power source during the short circuit in the electrode and the piece of work and a subsequent break of the circuit; 2) the analysis of stability and investigation of transition processes in a self-controlled system taking into account the inertness of the power source; 3) the investigation of the power source in a self-controlled system with periodic disturbances in the arc. The authors investigated the problems connected with the dynamics of power sources in automatic shieldedarc welding with fused electrodes and come to the following conclusions:

Card 1/3

125-1-7/15

Problems of the Dynamics of D.C. Power Sources for Automatic Shielded-arc Welding

The initial arc excitation and the stability of the welding process with short arcs can be improved by increasing the incremental rate of the short circuit current and the regenerating rate of the generator voltage during the break of the short-circuited welding chain. This may be attained by increasing the idle running voltage, by reducing the induction between the rotor circuit and the excitation coil and by reducing the time-constant of the rotor circuit.

An automatic control of the arc may be improved by using power sources with rigid or incremental characteristics. The slope of the external characteristics must be less than the slope of the volt-ampere static characteristics, in order to increase the stability of the system and to obtain aperiodic transient processes.

The authors propose that a generator with an independent excitation be utilized where the increased voltage of idle running can be obtained by a special circuit. Such generators have good dynamic properties and ensure a sufficient

Card 2/3

125-1-7/15

Problems of the Dynamics of D.C. Power Sources for Automatic Shielded-arc Welding

intensity of automatic control.

There are 2 figures and 3 Russian references.

ASSOCIATION: The Section of Power Sources and Automation of TSNIL Electrom

(Otdel istochnikov pitaniya i avtomatizatsii TsNIL-Elektrom)

of the USSR Academy of Sciences.

SUBMITTED: 2 April, 1957.

AVAILABLE: Library of Congress

Card 3/3

SOV/135-58-12-2/20

AUTHOR:

Rabinovich, I.Ya., Candidate of Technical Sciences

TITLE:

Problems in the Development of Electric Arc Welding Equipment (Voprosy razrabotki oborudovaniya dlya dugovoy elektricheskoy

i a tortani de la compani de la la compani de la compa

svarki)

PERIODICAL:

Svarochnoye proizvodstvo, Nr 12, pp 6-9 (USSR)

ABSTRACT:

General information is given on the development of electric arc welding equipment, such as transformers, generators, etc. The design of a.c. power sources was improved. The design of welding generators with universal external characteristics was developed at TsNIL-ELEKTROM under the supervision of G.M. Kasprzhak, I.Ya. Rabinovich and with the participation of Ye. I. Slepushkin, V.M. Shchitova, M.Sh. Dobrushin, N.V. Belenko and Ye.L. Orkina. Best results were obtained by using systems with excitation from semi-conductor or magnetic amplifiers. A test model of an attachment with a semi-conductor amplifier was designed under the supervision of G.M. Kasprzhak and with the participation of N.V. Belenko and Ye.L. Orkina. New automatic welding machines are equipped with an electrode feed from a stabilized drive (designed at TsNIL-ELEKTROM AS USSR

Card 1/2